



OVERVIEW

VTA29 Series is a next-generation aggregation 10GE switch introduced by Voltan Technology. It is targeted at the IP MAN (metropolitan area network), government and enterprise networks, Internet café and diskless working environment. It is developed on the basis of high performance hardware and VROS software platform with Voltan own independent intellectual property rights. It supports functions such as powerful ACL, flexible QinQ, 1:1 or N:1 VLAN switching, Ethernet OAM, carrier-level QoS and industry-level 10GE Etherring, ensuring this switch series meets application requirements in all kinds of complicated sites. It also supports layer-3 routing protocol. Voltan VTA29 Series has 2 models: VTA29-48P6X, VTA29-48P6X-370.

CHARACTERISTICS

Innovative Virtual Cluster Switching Technique

Innovative Voltan Virtual Switch System: VTA29 Series virtualizes multiple physical devices into one. The performance, reliability and management of the virtual system are superior to the physical ones.

Improved Performance: Voltan Virtual Switch System makes full use of each link in the physical devices, which avoids STP blocking the link and protects the original link to the maximum extent.

High Reliability: Based on the advanced distribution mechanism and efficient cross-physical link aggregation link function, the logic control plane, service control plane and service data plane are separated. Thus, VTA29 Series can support continuous layer-3 routing forwarding, avoiding service interruption as a result of a single point of failure.

Easy Management: Voltan Virtual Switch System realizes single IP management, greatly improving the networking efficiency and lowering the operating cost.

Industrial Ethernet Ring with Zero Delay and Zero Packet Loss

Supports industry-level EAPS and their protection shift time is less than 50ms. Their high reliability is represented by the null packet loss, which has been proved by many years of application in the Grid, rail transportation and defense systems.

Telecom-Level Ethernet Switch

Supports the telecom-level Ethernet-ring protection protocol with a protection shift time of less than 50ms, STP/RSTP/MSTP, backup of active and standby uplinks and LACP link aggregation to cater to the requirements of high reliability of carriers.

Support Ethernet standard 802.3u, 802.3x, 802.3ad, 802.1d, 802.1p, 802.1q, 802.1w, 802.1ad.

Support system status LED, port dynamic LED.

Provides the perfect Ethernet OAM mechanism to monitor the network running status in real time for rapid trouble locating and detection.

Supports powerful ACL functions to access and control L2 L7 data based on physical port, VLAN, MAC, IP and protocol port ID, and providing carriers flexible and various policy control methods.

Supports In-Service Software Upgrade (ISSU) to ensure the unremitting data forwarding during system upgrade.

Supports various L2 multicast functions, including IGMP-Snooping, fast-leave and trans-vlan multicast copy.

Flexible and Convenient Management and Maintenance

Supports management modes such as the console port, Telnet, SSH, etc.

Supports the WEB management mode, which is easy and efficient so that it makes installation and debugging convenient.

Supports TFTP-patterned file upload/download management.

Supports ISSU (In-Service Software Upgrade). Supports SNMP and Voltan NMS smart network management platform to realize automatic equipment discovery, network topology management, equipment configuration management, performance data statistics and analysis and trouble management

CHARACTERISTICS

Carrier-Level QoS Policies

Supports priority retagging and complicated flow classification based on VLAN, MAC, source address, destination address, IP or priority to better streamline carrier's services.

Supports provides flexible bandwidth control policies and supports port-/flow-based flow limit, and ensuring the line speed forwarding of each port to make sure the high quality of video, audio and data services.

Supports 8 priority queues by each port.

Supports multiple queue schedule algorithms such as SP, WRR, and SP+WRR.

Versatile IPv6 Solutions

Supports the IPv6 protocol suite, IPv6 neighbor discovery, ICMPv6, path MTU discovery, etc. Supports Ping, Traceroute, Telnet, SSH, ACL and so like on the basis of IPv6, meeting IPv6 networks' equipment management requirements and service control requirements.

Perfect Security Mechanisms

Equipment-level security: The advanced hardware infrastructure design realizes the level based packet schedule and packet protection prevents DoS-/TCP related: SYN flood, UDP flood, broadcast storm or large traffic attacks, and supports level-based command line protection, endowing different levels of users with different management permissions.

Supports perfect security authentication mechanisms: IEEE802.1x Radius and Tacacs+.

Supports storm/multicast/unicast limit to ensure the normal running of equipment in harsh network conditions.

Supports a perfect ring detection mechanism to ensure the long-term stable running of network. supports port isolation within the same VLAN DHCP-Snooping and IP plus MAC plus Port binding for ensuring user data security.

Intelligent PoE+

VTA29 series supports IEEE 802.3af/at PoE standard, and PoE power budget up to a maximum of 760W;

VTA29 series supports PoE non-stop power supply, the PoE+ power is maintained during a switch reload;

VTA29 series supports manual and dynamic PoE power allocation; VTA29 series supports up to 6KV thunder-proof of the PoE port and power supply.

MODEL

VTA29-48P6X



- 48-Port Gigabit PoE+
- 6-Port 10G/GE SFP+
- 370W AC PoE Budget
- 740W DC PoE Budget

VTA29-48P6X-370



- 48-Port Gigabit PoE+
- 6-Port 10G/GE SFP+
- 370W AC PoE Budget

SPECIFICATIONS		VTA29-48P6X	VTA29-48P6X-370
Gigabit PoE+		48	48
10G/GE SFP+		6	6
Console(RJ45)		1	1
Backplane(Gbps)		216	216
Forwarding rate (Mpps with 64 bytes)		162	162
Chassis	Dimensions (WxDxH)(mm)	440x280x44	440x280x44
	Weight (KG)(empty)	5.2	5.2
Package	Dimensions (WxDxH)(mm)	576x448x94	576x448x94
	Weight(KG)	6.1	6.1
Power consumption	no-load	< 25W	< 25W
	full-load	< 48W (without PoE)	< 48W (without PoE)
Power supply	AC: 100V-240V, DC: 36-72V	450W AC and 800W DC	450W AC
POE budget		370W@AC, 740W@DC	370 W
Total output BTU (1000BTU/H=293W)		1535.84@AC, 2730.38@DC	1535.84
Fan number		2	2
Noise@25°C(dBA)		45	45
MTBF(H)		>200,000	>200,000
Forwarding mode		Store-forward	Store-forward
Flash (MB)		16	16
DRAM (MB)		512	512
MAC		32K	32K
Buffer size(MB)		2	2
Interface vlan		64	64
Routing table		512	512
Jumbo frame		9K	9K

FEATURES

VLAN

- 4K Active VLAN,
- QinQ & Selective QinQ,
- GVRP, Private VLAN,
- Voice VLAN

Spanning Tree

- 802.1D (STP), 802.1W(RSTP) and 802.1S(MSTP)
- BPDU guard, root guard and loopback guard

Multicast

- IGMP v1/v2/v3
- IGMP Snooping
- IGMP Fast Leave
- IGMP Filter
- MVR

IP

- Static route
- RIP, OSPF
- IPv4/v6 dual stack

IPv6

- ICMPv6, DHCPv6, ACLv6 and Ipv6 Telnet
- IPv6 neighbor discovery, Path MTU discovery
- MLD V1/2, MLD snooping IPv6 Static Routing, RIPng, OSPFv3
- Manual tunnel, ISATAP tunnel, 6 to 4 tunnel

QoS

- CAR, HQoS, MAC/IP/TCP/UDP/ VLAN/ COS/DSCP/TOS based
- QoS, 802.1P/DSCP priority re-labeling, SP, WRR, and "SP+WRR",
- Tail-Drop, WRED, flow monitoring and traffic shaping

Security

- Port isolation, Port security, and "IP+MAC+port" binding, MAC sticky DHCP Snooping and option 82, DAI& IP source guard, PPPoE+,
- IEEE 802.1x, Radius and BDTacacs+
- L2/L3/L4 ACL flow identification and filtration Anti-attack from DDoS, TCP's SYN Flood, UDP, Flood, etc.
- Broadcast/multicast/unknown unicast storm-control
- Md5, SHA-256, RSA-1024, AES256, etc.

DHCP

- DHCP server/relay/client
- DHCP snooping/option82

Certification

- CE, FCC, ROHS

Reliability

- Static/LACP link aggregation,
- Interface backup
- EAPS and ERPS
- ISSU uninterrupted system upgrade
- VVSS, up to 16-units per stack
- VRRP
- UDLD

Management

- Console, Telnet, SSH v1/2, HTTP,
- HTTPS, SNMP v1/v2/v3, RMON
- TFTP, FTP, SFTP
- NTP
- ZTP
- SPAN, RSPAN
- Dying gasp *
- syslog

Accessories

- Power cord, rackmount kits, console cable.

Environment

- Operating temperature/ humidity: 0°C -50°C ,10%-90% non-condensing
- Storage temperature/humidity: -20°C -70°C , 5%-95% non condensing

ORDERING INFORMATION

Part.No	Description
VTA29-48P6X	48-Port Gigabit PoE+ 6-Port 10G SFP+ L3-lite Stackable Managed Switch (AC-220V+DC 48V power supplies, 370W AC POE budget, 740W DC POE budget, with cooling fan; 1U; standard 19-inch rack-mounted installation)
VTA29-48P6X-370	48-Port Gigabit PoE+ 6-Port 10G SFP+ L3-lite Stackable Managed Switch (AC-220V power supply, 370W AC PoE budget, with cooling fan; 1U; standard 19-inch rack-mounted installation)

10GE Optical Modules	
VTSFP+TX	10GE SFP+ to RJ45 port module (10M/100M/1000M/2.5G/5G/10G)
VTSFP+SX	TE SFP+ multi-mode (300m, 850nm, LC)
VTSFP+LX-10	TE SFP+ single-mode (20Km, 1310nm, LC, DDM)
VTSFP+LX-20	100M SFP single-mode (15Km, 1310nm, LC, DDM)
VTSFP+LX-40-1310	TE SFP+ single-mode (40Km, 1310nm, LC, DDM)
VTSFP+LX-40-1550	TE SFP+ single-mode (40Km, 1550nm, LC, DDM)
VTSFP+LX-80	TE SFP+ single-mode (80Km, 1550nm, LC, DDM)
GE Optical Modules	
VTGSFP-TX-B	GE SFP-to-RJ45 module
VTGSFP-SX-D	GE SFP multi-mode (500m, 850nm, LC, DDM)
VTGSFP-LX-10-D	GE SFP single-mode (10Km, 1310nm, LC, DDM)
VTGSFP-LX-20-D	GE SFP single-mode (20Km, 1310nm, LC, DDM)
VTGSFP-LX-40-D	GE SFP single-mode (40Km, 1310nm, LC, DDM)
VTGSFP-ZX-80-D	GE SFP single-mode (80Km, 1550nm, LC, DDM)
VTGSFP-ZX-120-D	Gigabit SFP single-mode (120Km, 1550nm, LC, DDM)